

# AGIP 7007



Fully synthetic engine oil with reduced HTHS for the new vehicles of the VW Group starting from model year 2000 with LongLife-Service (WIV) for flexible oil drain intervals, equipped with pump-injector diesel engines which require a lubricant meeting the Volkswagen 506.01 service specification. The product is also suitable to lubricate gasoline or diesel engines requiring lubricants meeting the Volkswagen 503.00 and 506.00 service specifications respectively.

## CHARACTERISTICS (TYPICAL FIGURES)

### AGIP 7007

<b>SAE Grade</b>		<b>0W-30</b>
Viscosity at 100°C	mm <sup>2</sup> /s	9,6
Viscosity at 40°C	mm <sup>2</sup> /s	53
Viscosity Index	-	167
Flash Point (open cup)	°C	223
Pour Point	°C	-39
Mass Density at 15°C	kg/m <sup>3</sup>	856

## PROPERTIES AND PERFORMANCE

- Fully synthetic high technology fuel efficient oil which meets the special requirements for flexible oil drain intervals (WIV) allowed by the VW specification 503.00, 506.00 and 506.01. Agip 7007 is by name officially approved by the VW Group.
- Characteristics for Agip 7007 are: excellent wear protection, excellent flowability at low temperatures, optimum lubrication also at the longest oil drain intervals, reduced HTHS viscosity which allows maximum reduction of fuel consumption.
- This product is not recommended for every type of vehicle. Please observe the manufacturer's specifications when selecting products.

## SPECIFICATIONS

AGIP 7007 is officially approved or meets the requirements of the following services and specifications:

- ACEA A5, B5
- Volkswagen 503.00, 506.00, 506.01