




EVOLUTION SXR 5W-40



Very high performance lubricant based upon ELF synthetics technology, designed for lubricating all Diesel car engines.

APPLICATIONS

All Diesel engines, especially those of recent technology

Even in very severe conditions

Fast driving

All times of year, even the coldest weather

- Recommended for all supercharged or naturally aspirated Diesels in cars and light vans.
- Suitable for all types of service (urban, or on the highway or motorway) especially in very severe conditions.
- For all types of driving, especially at high speed.
- Specially designed to meet the demands of the motor manufacturers as regards extended oil-change intervals.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications

ACEA 2004: A3/B4
API: SM/CF

OEMs approvals

RENAULT : RN0710, RN0700 : gasoline, turbo gasoline and Diesel without Diesel Particulate filter, 2.2 dCi DPF

CUSTOMER BENEFITS

Best possible performance

Excellent engine cleanliness and protection

Easier starting in very cold conditions

Longer engine life

Extended oil-change intervals

- Excellent engine protection, particularly against wear in the timing system.
- Ensures an exceptionally clean engine.
- Outstanding thermal stability and oxidation resistance, guaranteeing that the oil will not degrade even in conditions of very severe use.
- Immediate lubrication of engine components during cold starts, leading to longer engine life.
- Lubricant performance sustained over time for extended oil change intervals.

CHARACTERISTICS

ELF EVOLUTION SXR 5W-40	Method	Units	SAE Grade 5W-40
Density at 15°C	ASTM D1298	kg/m ³	854
Viscosity at 40°C	ASTM D445	mm ² /s	82.2
Viscosity at 100°C	ASTM 445	mm ² /s	13,6
Viscosity Index	ASTM D2270	-	169
Pour Point	ASTM D97	°C	-39
Flash Point	ASTM D92	°C	226
B.N.	ASTM D2896	mgKOH/g	9

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

Elf Evolution SXR 5W-40
Version july 07
MGP/07/07



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.