




PRESTIGRADE DIESEL 15W-40



Multigrade oil specially designed for Diesel engines in cars.

APPLICATIONS

Diesel engines

- Recommended for all Diesel engines in cars, MPVs and vans.
- The right lubricant for all types of service (urban use, on the highway or long motorway journeys) and for long-term use at all times of year.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications

ACEA: A3/B3
API: SL/CF

OEMs approvals

RENAULT Diesel (vehicles before 01.01.2001)
VOLKSWAGEN (performance level): VW 505.00
MERCEDES-BENZ: MB p. 229.1

CUSTOMER BENEFITS

Mineral technology oil dedicated to Diesel engines

- Specially developed for Diesel engines. Guarantees perfect engine lubrication.

CHARACTERISTICS

| PRODUCT NAME | Method | Units | SAE Grade |
|--------------------|------------|-------|-----------|
| Density at 15°C | ASTM D1298 | kg/m3 | 884 |
| Viscosity at 40°C | ASTM D445 | mm2/s | 103,2 |
| Viscosity at 100°C | ASTM 445 | mm2/s | 13,8 |
| Viscosity Index | ASTM D2270 | - | 136 |
| Pour Point | ASTM D97 | °C | -27 |
| Flash Point | ASTM D92 | °C | 230 |

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

Prestigrade Diesel 15W-40
Version Nov 05
MGP/11/05



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.