



TRACTELF BLS 90



Oil for axles equipped with limited slip differential systems for agricultural machinery and Public Works equipment.

APPLICATIONS

Limited slip differential axles

- Lubrication of axles equipped with limited slip differential systems for worksite equipment and agricultural machinery.
- May also be used in traditional hypoid axles not equipped with limited slip axles.

PERFORMANCES

API GL-5 "LS"

Approved by the manufacturers or meets the manufacturers' requirements

- Meets the international API GL-5 and MIL.L 2105B classifications
- Approved by the manufacturer ZF:
ZF TE ML 05C, 12C and 16E
- Suitable for lubrication of the specific axles for the following worksite equipment:
LIEBHERR
VOLVO
TEREX
CASE
JCB, etc.
And for front axles of four-wheel drive agricultural tractors:
CLAAS-RENAULT
STEYR
DEUTZ, etc.

CUSTOMER BENEFITS

Cleanliness

Comfort

Security

- Guarantees the high cleanliness of the limited slip disks installed in the axle
- Prevents noise and vibration under intensive use
- Thanks to its Extreme Pressure additives it provides maximum protection of very highly loaded gears and gears subject to shocks
- Excellent compatibility with the disk friction materials
- Excellent performance with respect to seals

CHARACTERISTICS

TRACTELF BLS	Units	90
Density at 15°C		0.899
Viscosity at 40°C	mm ² /s	166
Viscosity at 100°C	mm ² /s	17
Viscosity index		109
Pour point	°C	-33

The values of the specifications show in this table are typical values given as an indication only.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

TRACTELF BLS 90
June 2006
N°MPR 06/06



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.