



DEXRON III

**Fluid for automatic gearboxes
Power steering systems
Torque converters and hydraulic systems**

TECHNOSYNTHÈSE

TYPE OF USE

All systems when DEXRON or MERCON standard is required :

Automatic gearboxes, torque converters, power steering systems, boat reversing gears, hydrostatic transmission and hydraulic or mechanical systems that require Dexron ou Mercon standards.

PERFORMANCES

PERFORMANCE GENERAL MOTOR DEXRON III F-30336
 FORD MERCON M 950805 et M 941108
 ALLISON C4-23472696, CATERPILLAR TO-2, VOITH, ZF

More fluid at low temperature than Dexron IIE oils, allows easier gear change in cold wheather.
Higher oxidation resistance than Dexron IIE standard.
Oil film stability under high temperature.
Anti-wear, Anti-corrosion, Anti-foam.

RECOMMENDATION

MOTUL DEXRON III can be used (and mixed) for applications where "DEXRON" , "B DEXRON" , "DEXRON II D", "DEXRON IIE", or "DEXRON III" is required.

Oil change : according to manufacturers' recommendations and to be adapted according to your own use.

PROPERTIES

Color	Visual	Red
Density at 15°C (59°F)	ASTM D1298	0.857
Viscosity at 100°C (212°F)	ASTM D445	7.5 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	35.7 mm ² /s
Viscosity index	ASTM D2270	192
Flash point	ASTM D92	208°C / 406°F